



B-056.201P(B-056-1)

| REV. | REVISIONS | REC. | REV. | REVISIONS | REC. |
|------|--------------------------------|------|------|-----------|------|
| 1 | CANCEL (M),(O); UPDATE DRAWING | | | | |
| | | | | | |

| | | | | | |
|--|------------------|----------------|------------|----------------------------------|-----------------------------|
| DRAWN & DRAFTED BY YU ZHIHUA | TOLERANCES | | ANGLE: ±1° | TITLE: T-H BOBBIN RM-12 (2 SEC) | |
| | 0 < L ≤ 4 ±0.1 | pin pitch ±0.2 | UNIT: MM | BOBBIN MATERIAL: PHENOLIC PM9630 | UL REC. UL 94V-0 |
| CHECKED & APPROVED BY JOHN ROGN | 4 < L ≤ 16 ±0.2 | | ORIGIN: SZ | PIN MATERIAL: CP WIRE | PIN TENSION LOAD: 1.0KG MIN |
| | 16 < L ≤ 63 ±0.3 | | | DATE: MAR.31 '2003 | DRAWING NO. P-1213 |
| PIN SHINE INDUSTRIAL CO., LTD. TEL: 886-2-22990545 FAX: 886-2-22990546 | | | | | REV. 1 |